

DORTEK STAINLESS STEEL TRANSFER HATCH

Fire Resistant

Supplied By : DorteK Ltd St Mark Street Hull HU8 7ED United Kingdom
Tel +44 (0)1482 226848 Fax +44 (0) 1482 226843 e-mail info@dortek.com

Fire Resistant up to 60 minutes: These pass through hatches are manufactured using certified fireproof materials but have not been officially tested.

Sizes : Available in bespoke sizes on request.

Example Dimensions

External : 720*x720*x494 mm (WxHxD) Internal : 600x600x450 mm (WxHxD)

*S/O : Allow +10mm for structural opening

Hatch Panels and Architraves

Inner Panels : 1.5mm thick, 304 or 316L grade stainless steel.

Outer Body : 1.5mm thick, 304 or 316L grade stainless steel.

Fixed Flange: 2mm thick, 304 or 316L grade stainless steel.

Fixing : No visible fixings on the architraves

Seal to Wall : Mastic bead from the architrave to the wall finish on both sides of the vision Panel.

Finish : 240 grit

Doors

Door Type : Stainless steel, 1.5mm thick material

Vision Panel : Clamped Pyran S glass F60 or Pyrobelite glass F30

Finish : Glass clear, stainless steel 240 grit

Hinges : White polyamide encapsulated or stainless steel surface mounted hinges

Handle : 1 stainless steel lever handle per door

Interlock

Mechanical : Mechanical Interlock

Seal

Door Seal : Silicone seal with vulcanized corners, mechanical fixed to the hatch body

Intumescent : Fitted with intumescent seal to perimeter at door frame