

L20/480 TRAFFIC GRP SWING DOOR SETS

Dortek R Type Double Action Swing Doors

- Manufacturer : Dortek Ltd St Mark Street Hull HU8 7ED United Kingdom
Tel +44 (0) 1482 226848 Fax +44 (0) 1482 226843 e-mail: info@dortek.com
- Door : The doors shall be glass-fibre reinforced polyester moulded around non-organic hi-density core closed cell core with integral anodised aluminium edges incorporating a four sided replaceable neoprene gasket
- Reference : Dortek Type R Single -DA double action *or* Pair -DA double action
- Sizes : *See list of manufacturers standard sizes.*
- Core : High density closed cell C.F.C and HFC free. Thermal conductivity 0.50 W/m sq.
- Facing : Hygienic moulded polyester, 2.5mm thick. Moisture absorption zero.
- Door leaf : 22mm thick.
- Finish : Smooth non-porous gelcoat finish with built in colour
- Colour : Standard Super White 337 *or choice of 20 colours see chart or RAL / BS to order*
- Door frame : 40 x 80 RHS Steel Frame *or* Steel profile frame to suit wall thickness. Finish stainless steel *or* powder coated *or* anodised aluminium to suit wall thickness. *Specify wall thickness or Clients own frame specify material and size*
- Hinges : Dortek self closing gravity double action 240 degree swing hinge system consisting of V-cam solid cast hinge body and high performance sealed for life bearing with aluminium impact proof bottom pivot with steel shaft and self lubricating bearings.
- Glazing : Acrylic panel 185 x 735mm in single piece unbreakable frame. *optional for DDA compliance.* Acrylic panel 185 x 300mm positioned at low level to comply with DDA regulations.
- Protection : 3mm thick ribbed rubber standard colour grey, *or* 2mm thick smooth finish high impact grey PVC *or* 0.7mm thick stainless steel, bonded to door leaf *or* black polypropylene bumpers 290mm deep *or* 490mm deep
- Fixing : Fix direct to structure with stainless steel screws.