
L20/480 HERMETICALLY SEALING SLIDING DOORSETS

Dortek MF5 Type Hermetically Sealing Sliding Door Sets

- Manufacturer : Dortek Ltd St Mark Street Hull HU8 7ED United Kingdom Tel +44 (0)1482 226848
Fax +44 (0) 1482 226843 e-mail info@dortek.com
- Door : Flush 60mm core faced with 1mm plastic laminate. Framed in anodised aluminium Profile.
- Reference :
- Sizes : *See list of manufacturers standard sizes*
- Core : 48mm PU core
- Facing : 1mm hard plastic laminate on 5mm board / 6mm hard plastic laminate
- Door leaf : 60mm thick.
- Finish : Self finished
- Colour : Standard white *or* choice of colours see chart *or* RAL / BS to order.
- Door frame : Anodised aluminium corner profile
- Fire Rating : As building regulations and fire officer requirements tested to EN
- Ironmongery : Stainless steel lever handle both sides
- Track : MF5 Anodised aluminium track with nylon bearings
- Guide : Internal bottom track with nylon guide
- Glazing : Triple glazed with laminate safety glass outer panes finished flush with both faces of door, centre pane Georgian wired *or* ceramic glass, (30 & 60 min doors only)
Size 200 x 300mm *or* 200 x 600mm *or* 300 x 600mm *or* 400 x 600mm
- Canopy : Stainless steel, PPC steel or aluminium with sloping top.
- Operation : Electrical automation microprocessor controlled with safety photo-cell, in-built safety sensor to open the door if obstructed operated with 2 push buttons *or* 2 touchless sensors *or* 2 infra red detectors.
Specify Battery back-up to operate door in case of power failure