

488 DORTEK 'S' TYPE GRP DOUBLE ACTION CRASH DOORS

- Manufacturer: Dortek Ltd., St Mark Street, Hull, HU8 7ED, England; Tel: 01482 226848; Fax: 01482 226843;
E-mail: sales@dortek.com; Web: www.dortek.com;
 - Product reference: 'S' Type GRP Double Action Swing Doors by Dortek Ltd.
- Dortek 'S' Type Double Action Swing Doors:
 - Door leaf: The door blades are solid seamless moulded glass-fibre reinforced polyester. The door blade tapers nominally from 7mm to 4.5mm thick and has a 40mm thick spine.
 - Finish: Smooth non-porous gelcoat finish with built in colour –any RAL colour is available.
 - Frame: 40mm x 80mm RHS (Rolled Hollow Steel) frame powder coated to any colour.
 - Glazing details: single glazed acrylic vision panels per blade
Top: 200x600/700/900mm c/w aluminium frame Bottom: 200x300mm c/w aluminium frame.
 - Hinges: Delrin self lubricating nylon spring hinges with 180 degree swing.
Options: no stay, hold open or stop / no stop. 3no. per blade
 - Fixing: In accordance with manufacturer's recommendations and dependant on wall type.
 - Protection: Polypropylene spring bumpers to both sides of each blade; colour - black. 4no. per blade. PVC seal in aluminium carrier to the full height of the leading edge on each blade.
Option: PVC seal in aluminium carrier to the full height of the hinge edge on each blade.
Option: Grey rubber cladding 300mm x 900mm high to both sides of each blade.